

AD-2045 UL/CSA Certified

Magnetic Wet Bench with AC and DC Magnetization

The AD-2045 UL/CSA Certified Unit is designed, built, and certified to UL/CSA 61010-1 by a third party Nationally Recognized Testing Laboratory (NRTL).

This magnetic bench provides 4,000 amps of Alternating Current and 5,000 amps of 1-phase Full Wave Direct Current magnetization for finding surface and sub-surface defects during wet method magnetic particle inspection.

The two outputs are independently adjustable to set each magnetic field, circular or longitudinal.



BENEFITS

Unit designed to UL 61010-1 and CAN/CSA-C22.2 NO 61010-1

- Unit shipped with UL/CSA sticker from the Magnaflux Production Facility
- Standard components are further guarded, insulated, and shielded for added protection
- Unit is provided with Emergency Stop buttons which will shut off any in-progress magnetic current flow and dump air from the system to stop all movement
- A shorter stroke on the headstock is used to avoid pinch points

Faster part processing

- Reduce processing time with operator-enabled automatic Double-Mag Shot
- Generate 300+ shots per hour at maximum unit output

Real-world dependability for minimal downtime

- Allen-Bradley PLC provides reliable controls and off-the-shelf replacements
- Advanced agitator system helps prevent blockages and clumping by keeping magnetic particles well suspended
- Rely on our industry leading warranty with best in-class service delivered by a global network of trained Magnaflux authorized service centers

Easy to use and maintain

- Make quick operational adjustments using the simple, user-friendly operator interface with touch-screen controls
- External pump system provides fast access for easy cleaning and service
- Assure testing accuracy and repeatability with direct amperage rol and fluctuation mitigation

STANDARD FEATURES

- 5% duty cycle of 0.5 seconds on, 10 seconds off at maximum output
- Allen-Bradley PLC
- Control Circuit feedback loop for amperage regulation and repeatability
- Simple touch-screen operator interface
- External pump system for particle bath agitation, circulation and application
- Integrated decaying-AC demagnetization with 1-touch control
- Low-voltage output minimizes electrical exposure for operator safety
- Adjustable mag shot time from 0.5 to 2 seconds
- Automatic Double-Mag Shot with 1-touch control
- Mag-shot-activating front push bar with 1-touch control to enable/disable this feature
- Current assurance indicator light confirms magnetizing current delivery
- Solid state circuitry increases lifetime and performance of machinery

UPGRADE OPTIONS

- Inspection Enclosure Hood with ventilation fan for a darkened inspection area without sacrificing function and operator comfort, includes an EV6000 LED UV lamp, flame resistant curtains and visible lighting
- ST700 stationary overhead LED UV lamp, 100-240 V, 50-60 Hz

CONFIGURATION OPTIONS

- Long Part Capacity to increase max clamping length to 102 in / 259 cm
- 16 in / 40 cm or 20 in / 50 cm Coil, or 19.5 in / 49 cm Clam-Shell Coil (instead of 12 in / 30 cm coil)

- Rotating Contacts with 70 lb / 31 kg part capacity minimizes part handling during inspection (minimum coil size required is 16 in / 40 cm, reduces part length capacity by 9 in / 23 cm, not compatible with Auto-Bath)
- Oversized Contact Assembly for headstock and tailstock, 12 x 12 in / 30 x 30 cm (minimum coil size required is 16 in / 40 cm)
- Reinforced Rail for heavier part load, 1,500 lb / 680 kg part capacity
- Dual-Touch Sensor eliminates risk of injury during pinch points

PRODUCT PROPERTIES

Magnetizing Current Capacity	AC 4,000 A FWDC 5,000 A
Maximum Part Length*	54 in / 137 cm <i>(102 in / 259 cm)</i>
Maximum Unsupported Part Weight Capacity Only using Head and tailstock mounted V-Blocks	<i>300 lb / 136 kg</i>
Maximum Supported Part Weight Capacity* (using rail-mounted steady rests) Both limits are considering the use of Rail Mounted Steady rest to help support part on rails	<i>700 lb / 317 kg</i>
Maximum Part Diameter	12 in / 30 cm <i>(16 in / 40 cm, 20 in / 50 cm)</i>
Particle-Bath Tank Capacity*	20 gal / 75 L <i>(32 gal / 121 L)</i>
Available Voltages	460 or 575 V
Available Frequencies	60 Hz

* Optional feature configurations shown in italics