

## SECTION 1: IDENTIFICATION

### 1.1. PRODUCT IDENTIFIER

Product name : ZL-37  
 Product code : Not Available

### 1.2. RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST

Use of the substance/mixture : Non-Destructive Testing

### 1.3. DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

<b>Manufacturer</b>	<b>Distributor</b>
Magnaflux	
155 Harlem Ave.	
Glenview, IL 60025 - USA	
T: 847-657-5300	

### 1.4. EMERGENCY TELEPHONE NUMBER

Emergency number : CHEMTREC 800-424-9300

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1. CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

#### GHS classification

Eye Dam. 1  
 Asp. Tox. 1

### 2.2. LABEL ELEMENTS

#### GHS labelling

Hazard pictograms (GHS) :



Signal word (GHS) : Danger

Hazard statements (GHS) : Causes serious eye damage. May be fatal if swallowed and enters airways.

Precautionary statements (GHS) : Wear eye protection/face protection. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations.

### 2.3. OTHER HAZARDS

No additional information available

### 2.4. UNKNOWN ACUTE TOXICITY (GHS)

Not applicable.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. SUBSTANCE

Not applicable

### 3.2. MIXTURE

Name	Product identifier	%
Distillates, petroleum, hydrotreated heavy naphthenic	(CAS No) 64742-52-5	36.80
Alcohols, C12-15, ethoxylated	(CAS No) 68131-39-5	5.02
Petroleum distillates, hydrotreated light	(CAS No) 64742-47-8	5.01
Triphenyl phosphate	(CAS No) 115-86-6	2.50
1H-Benz[de]isoquinoline-1,3(2H)-dione, 2-butyl-6-(butylamino)-	(CAS No) 19125-99-6	1.01

## SECTION 4: FIRST AID MEASURES

### 4.1. DESCRIPTION OF FIRST AID MEASURES

First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: If irritation occurs, flush skin with plenty of water. Get medical attention if irritation persists.
First-aid measures after eye contact	: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get medical attention immediately.
First-aid measures after ingestion	: If swallowed, do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.

### 4.2. MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

Symptoms/injuries after inhalation	: May cause respiratory tract irritation.
Symptoms/injuries after skin contact	: May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
Symptoms/injuries after eye contact	: Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

### 4.3. INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

## SECTION 5: FIREFIGHTING MEASURES

### 5.1. EXTINGUISHING MEDIA

Suitable extinguishing media	: Treat for surrounding material.
Unsuitable extinguishing media	: Do not use water jet.

### 5.2. SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE

Fire hazard	: Products of combustion may include, and are not limited to: oxides of carbon, phosphorus oxides, nitrogen oxides, toxic gases, toxic vapours.
-------------	---

### 5.3. ADVICE FOR FIREFIGHTERS

Protection during firefighting	: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).
--------------------------------	--

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

General measures	: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.
------------------	--

### 6.2. METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP

For containment	: Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
Methods for cleaning up	: Scoop up material and place in a disposal container.

### 6.3. REFERENCE TO OTHER SECTIONS

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

## SECTION 7: HANDLING AND STORAGE

### 7.1. PRECAUTIONS FOR SAFE HANDLING

Precautions for safe handling	: Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke.
Hygiene measures	: Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

### 7.2. CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Storage conditions	: Keep out of the reach of children. Keep container tightly closed.
--------------------	---

### 7.3. SPECIFIC END USE(S)

Not available.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. CONTROL PARAMETERS

Distillates, petroleum, hydrotreated heavy naphthenic (64742-52-5)		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> /8h (inhalable fraction)
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> /8h
USA - NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> /10h (mist)
USA - NIOSH	NIOSH REL (STEL) (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> /15 minutes (mist)

Alcohols, C12-15, ethoxylated (68131-39-5)		
ACGIH	Not applicable	
OSHA	Not applicable	

Petroleum distillates, hydrotreated light (64742-47-8)		
ACGIH	ACGIH RCP-TWA (mg/m <sup>3</sup> )	1200 mg/m <sup>3</sup> (143 ppm) (total hydrocarbons; supplier exposure limits)
OSHA	Not applicable	

Triphenyl phosphate (115-86-6)		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup>
USA - IDLH	US IDLH (mg/m <sup>3</sup> )	1000 mg/m <sup>3</sup>
USA - NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup>

1H-Benz[de]isoquinoline-1,3(2H)-dione, 2-butyl-6-(butylamino)- (19125-99-6)		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (total dust) 3 mg/m <sup>3</sup> (respirable)
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> (total dust) 5 mg/m <sup>3</sup> (respirable)

### 8.2. EXPOSURE CONTROLS

Appropriate engineering controls	: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.
Hand protection	: Wear suitable gloves.
Eye protection	: Wear approved eye protection (properly fitted dust- or splash-proof chemical safety goggles) and face protection (face shield).
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Environmental exposure controls	: Maintain levels below Community environmental protection thresholds.
Other information	: Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: Liquid
Appearance	: Oily
Colour	: Green
Odour	: Mild
Odour threshold	: No data available
pH	: Neutral
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 235 °C (455°F) ASTM D-87

Flash point	: >93 °C (>200 °F)
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: Not flammable
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Vapour pressure	: No data available
Relative density	: 0.96
Relative vapour density at 20 °C	: No data available
Solubility	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: 12.36 - 15.10 @40°C (104°F)
Viscosity, dynamic	: No data available

## 9.2. OTHER INFORMATION

VOC content : 77 g/l

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. REACTIVITY

No dangerous reaction known under conditions of normal use.

### 10.2. CHEMICAL STABILITY

Stable under normal storage conditions.

### 10.3. POSSIBILITY OF HAZARDOUS REACTIONS

No dangerous reaction known under conditions of normal use.

### 10.4. CONDITIONS TO AVOID

Heat. Incompatible materials.

### 10.5. INCOMPATIBLE MATERIALS

Strong oxidizers, strong acids, strong alkalis, strong bases.

### 10.6. HAZARDOUS DECOMPOSITION PRODUCTS

May include, and are not limited to: oxides of carbon, phosphorus oxides, nitrogen oxides, toxic gases, toxic vapours.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. INFORMATION ON TOXICOLOGICAL EFFECTS

Acute toxicity : Not classified.

ZL-37	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 inhalation rat	> 20 mg/l/4h
Distillates, petroleum, hydrotreated heavy naphthenic (64742-52-5)	
LD50 oral rat	> 5000 mg/kg
Alcohols, C12-15, ethoxylated (68131-39-5)	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
Petroleum distillates, hydrotreated light (64742-47-8)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
LC50 inhalation rat	> 5000 mg/m <sup>3</sup> /4h

Triphenyl phosphate (115-86-6)	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	> 10000 mg/kg

Skin corrosion/irritation	: Based on available data, the classification criteria are not met.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitisation	: Based on available data, the classification criteria are not met.
Germ cell mutagenicity	: Based on available data, the classification criteria are not met.
Carcinogenicity	: Based on available data, the classification criteria are not met.
Reproductive toxicity	: Based on available data, the classification criteria are not met.
Specific target organ toxicity (single exposure)	: Based on available data, the classification criteria are not met.
Specific target organ toxicity (repeated exposure)	: Based on available data, the classification criteria are not met.
Aspiration hazard	: May be fatal if swallowed and enters airways.
Symptoms/injuries after inhalation	: May cause respiratory tract irritation.
Symptoms/injuries after skin contact	: May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
Symptoms/injuries after eye contact	: Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. TOXICITY

Ecology - general : May cause long-term adverse effects in the aquatic environment.

### 12.2. PERSISTENCE AND DEGRADABILITY

ZL-37	
Persistence and degradability	Not established.

### 12.3. BIOACCUMULATIVE POTENTIAL

ZL-37	
Bioaccumulative potential	Not established.

### 12.4. MOBILITY IN SOIL

No additional information available

### 12.5. OTHER ADVERSE EFFECTS

Effect on the global warming : No known ecological damage caused by this product.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. WASTE TREATMENT METHODS

Waste disposal recommendations : This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible.

## SECTION 14: TRANSPORT INFORMATION

In accordance with DOT/TDG/IATA/IMDG	
DOT Ground	Not regulated
TDG	Not regulated
IATA	Not regulated
IMDG	Not regulated

### ADDITIONAL INFORMATION

Other information	: No supplementary information available.
Special transport precautions	: Do not handle until all safety precautions have been read and understood.


**SECTION 15: REGULATORY INFORMATION**

**15.1. FEDERAL REGULATIONS**

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

NFPA health hazard : 2  
 NFPA fire hazard : 1  
 NFPA reactivity : 0



**15.2. US STATE REGULATIONS**

ZL-37	
State or local regulations	This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

**SECTION 16: OTHER INFORMATION**

Date of issue : 02/17/2016  
 Revision date : 02/17/2016  
 Other information : None.

*Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.*